Application No. 10/566,935 Docket No.: 13111-00062-US Amendment dated November 21, 2008

After Final Office Action of July 23, 2008

AMENDMENTS TO THE CLAIMS

1-5. (Canceled)

6. (Previously presented) A process as claimed in claim 14, wherein the ionic liquid which

is recovered from the work-up stage is recirculated to the column.

7. (Previously presented) A process as claimed in claim 6, wherein the ionic liquid is

recirculated in an enrichment section of the column.

8. (Previously presented) A process according to claim 6, wherein the ionic liquid is

recirculated onto one of three uppermost plates in the column.

9. (Previously presented) A process according to claim 6, wherein the ionic liquid is

recirculated onto an uppermost plate in the column.

10. (Previously presented) A process for separating azeotropic or close-boiling mixtures by

subjecting the mixtures to extractive rectification in which ionic salts which are liquid at

temperatures below 200°C are used as entrainer, wherein a high-boiling bottom product is taken

off from a column in vapor form via a side offtake, wherein the side offtake is positioned in a

stripping section of the column which has a plurality of plates including three bottommost plates,

and wherein the side offtake is positioned directly at a bottommost plate in the column.

11. (Previously presented) A process for separating azeotropic or close-boiling mixtures by

subjecting the mixtures to extractive rectification in which ionic salts which are liquid at

temperatures below 200°C are used as entrainer, wherein a high-boiling bottom product is taken

off from a column in vapor form via a side offtake, wherein a bottom stream which has been

5

Application No. 10/566,935 Docket No.: 13111-00062-US Amendment dated November 21, 2008

After Final Office Action of July 23, 2008

depleted in high boilers is recirculated to the column, and wherein the bottom stream is recirculated in an enrichment section of the column.

12. (Previously presented) A process for separating azeotropic or close-boiling mixtures by subjecting the mixtures to extractive rectification in which ionic salts which are liquid at temperatures below 200°C are used as entrainer, wherein a high-boiling bottom product is taken off from a column in vapor form via a side offtake, wherein a bottom stream which has been depleted in high boilers is recirculated to the column, and wherein the bottom stream is recirculated onto one of three uppermost plates in the column.

- 13. (Previously presented) A process for separating azeotropic or close-boiling mixtures by subjecting the mixtures to extractive rectification in which ionic salts which are liquid at temperatures below 200°C are used as entrainer, wherein a high-boiling bottom product is taken off from a column in vapor form via a side offtake, wherein a bottom stream which has been depleted in high boilers is recirculated to the column, and wherein the bottom stream is recirculated onto an uppermost plate in the column.
- 14. (Currently amended) A process for separating azeotropic or close-boiling mixtures by subjecting the mixtures to extractive rectification in which ionic salts which are liquid at temperatures below 200°C are is used as entrainer, wherein a high-boiling bottom product is taken off from a column in vapor form via a side offtake, wherein the bottom stream from the column is passed to a work-up stage in which the ionic liquid present is submitted to vaporization in order for separation of high-boilers still present.
- 15. (Previously presented) A process for separating azeotropic or close-boiling mixtures by subjecting the mixtures to extractive rectification in which ionic salts which are liquid at

Application No. 10/566,935

Amendment dated November 21, 2008

After Final Office Action of July 23, 2008

temperatures below 200°C are used as entrainer, wherein a high-boiling bottom product is taken

Docket No.: 13111-00062-US

off from a column in vapor form via a side offtake, wherein the bottom stream from the column

is passed to a work-up stage in which the ionic liquid present is submitted to stripping in order

for separation of high-boilers present.

16. (Previously presented) A process as claimed in claim 15, wherein the ionic liquid which

is recovered from the work-up stage is recirculated to the column.

17. (Previously presented) A process as claimed in claim 16, wherein the ionic liquid is

recirculated in an enrichment section of the column.

18. (Previously presented) A process as claimed in claim 16, wherein the ionic liquid is

recirculated onto one of three uppermost plates in the column.

19. (Previously presented) A process according to claim 16, wherein the ionic liquid is

recirculated onto an uppermost plate in the column.

7